

PRODUCT NO. 5043

LED power supply CC for QUICK-FIXdc 15-50W 350-1400mA 25-54V non-dimmable NFC linear pre-programmed outputs 350/700/1050/1400mA



to the product page

- SELV output protection for safety and flexibility in luminaires
- Very low current ripple, according to IEEE 1789 recommendation
- NFC technology for wireless programming
- Wide selection range for fixed current output
- Suitable for use in emergency lighting applications
- Active no-load protection
- Long life of up to 100,000 hours
- Ideal solution for Class I and Class II luminaires

Adjustable operating current: 350/700/1050/1400mA

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4226
WEIGHT IN KG	0.198
POWER CONSUMPTION IN WATTS	15-50

Dimensions

length: 280mm
width: 30mm
height: 21mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	186 - 240 AC/DC
Service life	
Output current in A	
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	80
PROTECTION CLASS	II
OVERVOLTAGE PROTECTION	1000 V
INPUT VOLTAGE SPAN	198-264 V AC / 186-280 V DC
WARRANTY IN YEARS	5
INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC / 186-280 V DC
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	Yes
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany