

PRODUCT NO. 5047

LED power supply CC for QUICK-FIXdc 6-50W 100-1400mA 25-54V DALI dimmable NFC linear
Factory setting 350mA/1400mA



to the product page

- DALI-2 certified LED driver, 1-100% dimming range
- SELV output protection for safety and flexibility in luminaires
- Amplitude dimming for highest quality light output, according to IEEE 1789 recommendation
- NFC technology for wireless programming
- Suitable for use in emergency lighting applications
- Ideal solution for Class I and Class II

Factory setting of operating current 350mA/1400mA

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.24	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	6-50	Output current in A	
		INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	85
		PROTECTION CLASS	II
		OVERVOLTAGE PROTECTION	1000 V
		OUTPUT VOLTAGE	25 - 54 DC
		INPUT VOLTAGE SPAN	198-264 V AC / 176-280 V DC
		WARRANTY IN YEARS	5
		DIMMING WITHOUT DIMMER	No
		INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC / 176-280 V DC
		ETIM GRUPPEN-ID	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	Yes
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No

Dimensions

length: 360mm
width: 30mm
height: 21mm

DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany