

PRODUCT NO. 5070-030036

DOTLUX LED tracklight SLIMtrack-eco 15W 3000K black



















to the product page

- EDISON® brand LED and flicker-free power supply unit
- Excellent price-performance ratio
- Natural color perception due to extra high CRI value
- Die-cast aluminum housing
- Passive cooling system without fan

SUCCESSION ARTICLE	5070-199036

WEIGHT IN KG 0.5
POWER CONSUMPTION IN WATTS 15
NET LUMINOUS FLUX IN LUMENS 1500
LUMEN PER WATT 100

Dimensions

length: 249mm diameter: 65mm BEAM ANGLE 36°
PROTECTION CLASS (IP) IP20
LIGHT COLOR white

INPUT VOLTAGE 220 - 240 V AC

SERVICE LIFE approx. 35.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 3000 **COLOR-RENDERING-INDEX** CRI > 92 POWER FACTOR 0,9 **INRUSH CURRENT IN A LUMEN PER WATT** 100 PROTECTION CLASS **HOUSING COLOUR** black **SWITCH CYCLES** > 70.000 **OVERVOLTAGE PROTECTION** 1500 V WARRANTY IN YEARS 3 **SIMILAR TO RAL-COLOUR** 9005 ASSORTMENT Ecoline

ENERGY EFFICIENCY CLASS

ACCORDING TO EU REGULATION

2019/2015

ETIM GRUPPEN-ID EC001744

MATERIAL COVER Plastic matt/satinized

DIMMING 0-10 V No
DIMMING 1-10 V No
DIMMING DALI No
DIMMING DMX No
DIMMING DSI No

not required



DIMMING POTENTIOMETER No (INTEGRATED) **DIMMING LINESWITCH** No **DIMMING MANUFACTURER'S** No PROPRIETARY SYSTEM **DIMMING MAINS VOLTAGE** No MODULATION **DIMMING PHASE CUT-OFF** No DIMMING PROGRAMMABLE No DIMMING RF No DIMMING SINE WAVE REDUCTION No **DIMMING TOUCH AND DIM** No DIMMING ZIGBEE No **DIMMING WITH PUSH-BUTTON** No DIMMING DEPENDING ON CONTROL No GEAR NO DIM FUNCTION Yes COLOUR CONSISTENCY (MCADAM SDCM6 ELLIPSE) **DIMMING DALI-2** DIMMING PHASE CUT-ON No **DIMMING GPRS** No PULSE DURATION IN µS 0 **BEG FUNDING** Only relevant in Germany DREH- /SCHWENKBAR 350°/90° **ENERGIEEFFIZIENZKLASSE DER** Ε LICHTQUELLE EINER LEUCHTE **COLOUR OF LIGHT ADJUSTABLE** No

Rotating and swivelling

ADJUSTABILITY