


PRODUCT NO. 5081-0275M

**DOTLUX LED strip SIDEVIEW 48W 8mm 2700K IP20 5m roll incl. 50cm connection cable on both sides**



to the product page

**ENERGY**

**DOTLUX**  
5081-0275M

A

B

C

D


E

F

G

**G**

**48**  
kWh/1000h



2019/2015

- Side-radiating, flexible LED strip, ideal for curved applications
- Cozy and lifelike light due to extra high color rendering RA>92
- Consistent color temperature due to 3-Step Mac Adam binning
- Very densely arranged LEDs allow homogeneous illuminated areas at smallest distances
- **Secure Solder Connect**Technology prevents failure of individual segments
- Reinforced copper conductors ensure uniform brightness
- Original 3M-VHB adhesive tape provides strong hold
- 50 cm connection cable pre-mounted on both sides

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.13
POWER CONSUMPTION IN WATTS	48
NET LUMINOUS FLUX IN LUMENS	3550

**Dimensions**

**length:** 5000mm  
**width:** 8mm  
**height:** 1mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	2700
COLOR-RENDERING-INDEX	CRI > 92
POWER FACTOR	0,9
AMOUNT OF LED/M	112
SEVERABLE BY MM	62,5
TC TEMPERATURE IN °C	67
OUTPUT W/M	9,6
LIGHT FLUX LM/M	710
PROTECTION CLASS	II
VOLTAGE TYPE	DC
SELF-STICKING	yes
INPUT VOLTAGE SPAN	24 V DC
WARRANTY IN YEARS	7
INPUT VOLTAGE RANGE LUMINAIRE	24 V DC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	G
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	50000
ETIM GRUPPEN-ID	ECO02706
DEGREE OF PROTECTION (NEMA)	1
CONSTANT LIGHT OUTPUT (CLO)	Yes

<b>TYPE OF WIRING</b>	Ending
<b>CONNECTION TYPE</b>	solder connection
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>MODEL</b>	Strip
<b>EXCHANGEABLE CONTROL GEAR</b>	Yes
<b>SUITABLE FOR DIMMER</b>	Yes
<b>LAMP TYPE</b>	LED not exchangeable
<b>WITH CONNECTION SET</b>	No
<b>WITH END PIECE</b>	No
<b>WITH PROTECTIVE COVER</b>	No
<b>MOUNTING METHOD</b>	Surface mounting/recessed mounting
<b>LIFETIME L70/B50 AT 25°C</b>	50000
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	-
<b>TYPE OF CONTROL GEAR</b>	Electronic transformer
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No