

PRODUCT NO. 3530-140180

DOTLUX LED light strip ENDLESS 600mm 8W 4000K

















- Direct connection to 230 V no external power supply required
- Impact-resistant housing made of shatterproof polycarbonate
- \"SEAMLESS CONNECT\" Hardly visible interruption due to the seamless connection
- \"DOT FREE\" design with uniform illuminated area
- Each light can be switched individually does not affect through-wiring
- Incl. seamless connector and cable connector (20 cm)
- Connection cable can be ordered separately
- In series connection, up to 10 light strips can be operated via one connection cable.

Dim	iens	ions

length: 572mm width: 22mm height: 32mm

BEAM ANGLE 150° PROTECTION CLASS (IP) IP20 **LIGHT COLOR** white INPUT VOLTAGE

220 - 240 V AC

SERVICE LIFE approx. 30.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 4000 COLOR-RENDERING-INDEX CRI > 82 **POWER FACTOR** 0,61 **INRUSH CURRENT IN A** Π **LUMEN PER WATT** 109 PROTECTION CLASS HOUSING COLOUR white **SWITCH CYCLES** > 60 000 INPUT VOLTAGE SPAN 220-240 V AC

WARRANTY IN YEARS

INPUT VOLTAGE RANGE LUMINAIRE 220-240 V AC

ASSORTMENT Ecoline

ENERGY EFFICIENCY CLASS

ACCORDING TO EU REGULATION 2019/2015

EC000109 ETIM GRUPPEN-ID DIMMING 0-10 V No **DIMMING 1-10 V** No DIMMING DALI No **DIMMING DMX** No DIMMING DSI No DIMMING POTENTIOMETER Nο

(INTEGRATED)

not required



DIMMING LINESWITCH No DIMMING MANUFACTURER'S No PROPRIETARY SYSTEM DIMMING MAINS VOLTAGE No MODULATION DIMMING PHASE CUT-OFF No **DIMMING PROGRAMMABLE** No DIMMING RF No DIMMING SINE WAVE REDUCTION No DIMMING TOUCH AND DIM No DIMMING ZIGBEE No DIMMING WITH PUSH-BUTTON No NO DIM FUNCTION Yes DIMMING PHASE CUT-ON No DIMMING GPRS No PULSE DURATION IN μS 0

BEG FUNDING Only relevant in Germany

ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE

COLOUR OF LIGHT ADJUSTABLE

COLOUR

White

DOTLUX LED light strip ENDLESS 600mm 8W 4000K