

PRODUCT NO. 3531-130180

DOTLUX LED light strip ENDLESS 900mm 12W 3000K



to the product page

- Direct connection to 230 V - no external power supply required
- Impact-resistant housing made of shatterproof polycarbonate
- \"SEAMLESS CONNECT\" - Hardly visible interruption due to the seamless connection
- \"DOT FREE\" design with uniform illuminated area
- Each light can be switched individually - does not affect through-wiring
- Incl. seamless connector and cable connector (20 cm)
- Connection cable can be ordered separately
- In series connection, up to 10 light strips can be operated via one connection cable.

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3531-040180
WEIGHT IN KG	0.16
POWER CONSUMPTION IN WATTS	12
NET LUMINOUS FLUX IN LUMENS	1300
LUMEN PER WATT	108

Dimensions

length: 872mm
width: 22mm
height: 32mm

BEAM ANGLE	150°
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 30.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,6
INRUSH CURRENT IN A	0
LUMEN PER WATT	108
PROTECTION CLASS	II
HOUSING COLOUR	white
SWITCH CYCLES	> 60.000
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	3
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ASSORTMENT	Ecoline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC000109
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No

DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	F
COLOUR OF LIGHT ADJUSTABLE	No
COLOUR	White