


PRODUCT NO. 1792-240180

DOTLUX LED tube LUMENPLUS 43,8cm/45cm 9W 4000K frosted rotating end cap special size



to the product page

- **TECHNICAL ADVANTAGES**
 - Internal aluminum heat sink enables optimized thermal management
 - Polycarbonate cover with UV-protective coating (non-yellowing)
 - Future-oriented due to individually replaceable power supply units
 - Individually adjustable light beam angle due to patented end cap
 - Fail-safe, as each individual LED is controlled separately
- **FURTHER ADVANTAGES OF THE LUMENPLUS TUBES**
 - 5 years Dotlux warranty on drivers and LEDs
 - Very easy replacement of fluorescent tubes with starter
 - Immediately the full, optimal light output after switching on
 - LM80 certified LEDs



SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	1792-140180
WEIGHT IN KG	0.135
POWER CONSUMPTION IN WATTS	9
CONSUMPTION (KWH/1000H)	9
NET LUMINOUS FLUX IN LUMENS	1440
LUMEN PER WATT	160

Dimensions

length: 435mm
diameter: 26mm

BEAM ANGLE	180°
PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 83
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
SPECIAL FEATURE	Flicker-free
LUMEN PER WATT	160
SWITCH CYCLES	> 100.000
COVER MATERIAL	Polycarbonate PC
WARRANTY IN YEARS	5
L/B VALUE	L80/B10
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	C
ETIM GRUPPEN-ID	EC001959
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
PULSE DURATION IN µS	0
OPTICS OF THE COVER	frosted
LIGHT COLOUR ACCORDING TO EN 12464-1	neutral white 3300 to 5300 K
BEG FUNDING	Only relevant in Germany
COLOUR	White