

PRODUCT NO. 3679-1

DOTLUX LED safety light EXITtop with self-test incl. 2 interchangeable lenses white 3h



to the product page

- Universally mountable safety light for recessed and surface mounting
- Replaceable rechargeable battery with a lighting duration of 3 hours
- Integrated pushbutton and control LED for operating status display
- Only suitable for stand-by mode. If the light is supplied with mains power, the integrated rechargeable battery charges and the light is in stand-by mode.
- Incl. two easy to change lenses
 - Corridor lighting (asymmetric)
 - Wide beam
- Automatic self-test function

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3679 3679-1
WEIGHT IN KG	0.433
POWER CONSUMPTION IN WATTS	0,5
NET LUMINOUS FLUX IN LUMENS	240

Dimensions

height: 62mm
diameter: 140mm

BEAM ANGLE	180°
PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	5000
POWER FACTOR	0,25
BATTERY RUNTIME	3h
PROTECTION CLASS	II
HOUSING COLOUR	white
INSTALLATION OPENING DIAMETER IN MM	120
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	3
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001957
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
MATERIAL COVER	Other