


PRODUCT NO. 1807-2FW120

DOTLUX LED panel FLATfrost 620x620mm 38W COLORselect



















- 3-Step MacAdam Binning Constant color temperature of all luminaires.
- High number of low-current LEDs guarantee long LED lifetime and consequently low maintenance costs!
- Glare-free, homogeneous and shadow-free light distribution
- Fatigue-free work due to flicker-free light
- Better contrast rendition with very good color rendering and constant color temperature
- White frame and connection cable with plug connector

SUCCESSION ARTICLE

1807-240120 1807-0FW120 PREDECESSOR ARTICLE

1807-1FW120

WEIGHT IN KG 1.9 POWER CONSUMPTION IN WATTS 38 **NET LUMINOUS FLUX IN LUMENS** max. 3610 **LUMEN PER WATT** 95

Dimensions

length: 620mm width: 620mm height: 14mm

BEAM ANGLE 120° PROTECTION CLASS (IP) IP20

LIGHT COLOR multicoloured

SERVICE LIFE approx. 50.000 h at 25°C **COLOR TEMPERATURE IN KELVIN** 3000/4000/5700

COLOR-RENDERING-INDEX CRI > 92 POWER FACTOR 0.9 **INRUSH CURRENT IN A**

IK protection

LUMEN PER WATT 95 PROTECTION CLASS HOUSING COLOUR white **SWITCH CYCLES** > 100.000 SIMILAR TO RAL-COLOUR 9016 **HCL-READY ASSORTMENT** Proline

ENERGY EFFICIENCY CLASS

ACCORDING TO EU REGULATION not required

2019/2015

ETIM GRUPPEN-ID EC002892

MATERIAL COVER Plastic matt/satinized

Yes

SDCM6

DIMMING DEPENDING ON CONTROL

GEAR

NO DIM FUNCTION Yes

COLOUR CONSISTENCY (MCADAM ELLIPSE)

IMPACT STRENGTH IKO2



COLOUR OF LIGHT ADJUSTABLE PULSE DURATION IN μS BEG FUNDING

ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE Positions

Only relevant in Germany

F