

PRODUCT NO. 5116

CASAMBI DALI interface/gateway passive



to the product page

CASAMBI to DALI gateway

Ideal for DALI group control (max. 64DALI devices with DALI power supply Art.5119)

- Up to 250 DALI devices per interface depending on the DALI power supply (max. 250mA=249 devices)
- Through-wirable DALI interface for convenient control of DALI light sources via Casambi app
- Suitable for integrating a conventional DALI sensor into the CASAMBI world
- passive device, external power supply via DALI cable required! Compatible with DALI power supply (item no. 5119)
- compatible with sensor (art. no. 5117), radio remote control (art. no. 5120) and wall switch (art. no. 5121)
- Various pre-installed profiles can be selected in the CASAMBI app
- Control of DALI components via CASAMBI
- Control of CASAMBI components via DALI
- DALI individual addressing or DALI group control/broadcast
- Complete control via CASAMBI app:
- Control of brightness and light color
- Configuration of luminaires and luminaire networks
- Creating scenes and animations (color gradients)
- Intelligent timer and gallery functions

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.02	INPUT VOLTAGE SPAN	9,5-22,5 V DC
		INPUT VOLTAGE RANGE LUMINAIRE	9.5-22.5 V DC
		ETIM GRUPPEN-ID	EC002924
		BEG FUNDING	Only relevant in Germany

Dimensions

length: 40mm

width: 36mm

height: 14mm