

PRODUCT NO. 5030-1

LED power supply CC 350-1050mA 40W 2-100V dimmable KNX/Push



to the product page

- Constant current power supply, which can be preset by DIP switch between 350 and 1050mA.

SUCCESSION ARTICLE	-	INPUT VOLTAGE	220 - 240 V AC
WEIGHT IN KG	0.248	OUTPUT CURRENT IN A	0,35-1,05
POWER CONSUMPTION IN WATTS	40	INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	90
		PROTECTION CLASS	II
		OVERVOLTAGE PROTECTION	3750 V
		OUTPUT VOLTAGE	2 - 100 DC
		INPUT VOLTAGE SPAN	180-295 V AC / 220-417 V DC
		WARRANTY IN YEARS	2
		INPUT VOLTAGE RANGE LUMINAIRE	180-295 V AC / 220-417 V DC
		ETIM GRUPPEN-ID	EC002710
		DIMMING PROGRAMMABLE	Yes
		DIMMING WITH PUSH-BUTTON	Yes
		NO DIM FUNCTION	No
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany

Dimensions

length: 124mm
width: 82mm
height: 23mm