


PRODUCT NO. 3140-1

LED power supply CC 9-15W 200-350mA 16W 26-42V dimmable phase section



to the product page

- The power supply is dimmable via phase cut dimmer
- With constant current technology (CC) it is suitable for constant current luminaires
- The connected constant current luminaires can be dimmed between 10%-100%
- Suitable dimmers: JUNG 1224 LED UDE, Eltako EUD61NPL-230V, GIRA Mini2440 00 and many more
- The output current is adjustable: 200/250/300/350mA
- The power supply is set to 200mA by default

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3140
WEIGHT IN KG	0.079
POWER CONSUMPTION IN WATTS	9-15

Dimensions

length: 122mm
width: 41mm
height: 23mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
OUTPUT CURRENT IN A	0,2-0,35
POWER FACTOR	0,98
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	85
PROTECTION CLASS	II
OVERVOLTAGE PROTECTION	1000 V
OUTPUT VOLTAGE	26 - 42 DC
INPUT VOLTAGE SPAN	180-264 V AC
WARRANTY IN YEARS	5
INPUT VOLTAGE RANGE LUMINAIRE	180-264 V AC
ETIM GRUPPEN-ID	EC002710
DIMMING MAINS VOLTAGE MODULATION	Yes
DIMMING PHASE CUT-OFF	Yes
NO DIM FUNCTION	No
DIMMING PHASE CUT-ON	Yes
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany