

PRODUCT NO. 4258-1

LED power supply CC 27-40W 700-1050mA 27-38V dimmable phase-on/phase-off















to the product page

- The power supply is dimmable via phase cut dimmer or phase angle dimmer
- With constant current technology (CC) it is suitable for constant current luminaires
- The connected constant current luminaires can be dimmed between 10%-100%
- Suitable dimmers: JUNG 1224 LED UDE, Eltako EUD61NPL-230V, GIRA Mini2440 00 and many more.
- The output current is adjustable: 700/800/950/1050mA
- The power supply is set to 700mA by default

SUCCESSION ARTICLE PREDECESSOR ARTICLE 4258

WEIGHT IN KG 0.15
POWER CONSUMPTION IN WATTS 27-40

Dimensions

length: 173mm width: 44mm height: 30mm PROTECTION CLASS (IP) IP20

 INPUT VOLTAGE
 220 - 240 V AC

 OUTPUT CURRENT IN A
 0,7-1,05

 POWER FACTOR
 0,97

 INRUSH CURRENT IN A
 0

TC TEMPERATURE IN °C 85

PROTECTION CLASS II

OVERVOLTAGE PROTECTION 1000 V

OUTPUT VOLTAGE 27 - 38 DC

INPUT VOLTAGE SPAN 198-264 V AC

WARRANTY IN YEARS

INPUT VOLTAGE RANGE LUMINAIRE 198-264 V AC **ETIM GRUPPEN-ID** EC002710

DIMMING MAINS VOLTAGE

MODULATION

DIMMING PHASE CUT-OFF Yes
DIMMING PHASE CUT-ON Yes
PULSE DURATION IN µS 0

BEG FUNDING Only relevant in Germany

Yes