


PRODUCT NO. 5151-040120

DOTLUX LED spotlight FLOORslim-sensor 50W 4000K black with motion detector PIR



|  |  |
|--|--|
| <b>DIMMING DMX</b>   | No                                     |
| <b>DIMMING DSI</b>   | No                                     |
| <b>DIMMING POTENTIOMETER (INTEGRATED)</b>                                    | No                                     |
| <b>DIMMING LINESWITCH</b>  | No                                     |
| <b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>                             | No                                     |
| <b>DIMMING MAINS VOLTAGE MODULATION</b>                                      | No                                     |
| <b>DIMMING PHASE CUT-OFF</b>   | No                                     |
| <b>DIMMING PROGRAMMABLE</b>  | No                                     |
| <b>DIMMING RF</b>  | No                                     |
| <b>DIMMING SINE WAVE REDUCTION</b>   | No                                     |
| <b>DIMMING TOUCH AND DIM</b>   | No                                     |
| <b>DIMMING ZIGBEE</b>  | No                                     |
| <b>DIMMING WITH PUSH-BUTTON</b>  | No                                     |
| <b>DIMMING DEPENDING ON CONTROL GEAR</b>                                     | No                                     |
| <b>NO DIM FUNCTION</b>   | Yes                                    |
| <b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>                                   | SDCM6                                  |
| <b>IMPACT STRENGTH</b>   | IK08                                   |
| <b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b> | No                                     |
| <b>DIMMING DALI-2</b>  | No                                     |
| <b>DIMMING PHASE CUT-ON</b>  | No                                     |
| <b>DIMMING GPRS</b>  | No                                     |
| <b>LIFETIME L70/B50 AT 25°C</b>  | 70000                                  |
| <b>LIFETIME L90/B10 AT 25°C</b>  | 20000                                  |
| <b>PULSE DURATION IN µS</b>  | 0                                      |
| <b>LIFETIME L90/B50 AT 25°C</b>  | 25000                                  |
| <b>BEG FUNDING</b>   | Only relevant in Germany               |
| <b>DREH- /SCHWENKBAR</b>   | Mounting bracket freely rotatable 320° |
| <b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>                  | E                                      |
| <b>COLOUR OF LIGHT ADJUSTABLE</b>  | No                                     |
| <b>ADJUSTABILITY</b>   | Swivelling                             |