

PRODUCT NO. 4997-040270


DOTLUX LED site socket with integrated bulb 12W 4000K



- Extremely high efficiency compared to conventional light bulbs
- Fastest installation due to two-pole quick-connect terminal block
- Anti-theft device



to the product page

**ENERGY**

**DOTLUX**  
4997-040270

A

B

C

D

E


F

G

F

12

kWh/1000h



2019/2015

SUCCESION ARTICLE	-
WEIGHT IN KG	0.06
POWER CONSUMPTION IN WATTS	12
NET LUMINOUS FLUX IN LUMENS	1150
LUMEN PER WATT	96

Dimensions

height: 280mm  
diameter: 65mm

BEAM ANGLE	270°
DIMMABLE	No
PROTECTION CLASS (IP)	IP40
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 25.000 h at 25°C
BASE	other
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
CONSTRUCTION	A-Type
POWER FACTOR	0,6
INRUSH CURRENT IN A	0.09
LUMEN PER WATT	96
HOUSING COLOUR	white
SWITCH CYCLES	> 50.000
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	2
RATED CURRENT	0.09
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ASSORTMENT	Ecoline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	F
ETIM GRUPPEN-ID	EC001959
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RGO

COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
LAMP SHAPE	Pear-shape
FILAMENT LAMP	No
LAMP DESIGNATION	A-Type
REMOTE OPERATION POSSIBLE	No
WITH REMOTE CONTROL	No
PULSE DURATION IN $\mu$ S	0
LIGHT COLOUR ACCORDING TO EN 12464-1	neutral white 3300 to 5300 K
BEG FUNDING	Only relevant in Germany
TYPE OF GLASS/COVER	Opal
COLOUR	White