

PRODUCT NO. 5157-040155

DOTLUX LED street light DOLPHINmicro 70W 4000K 1-10V dimmable without pole adapter

















to the product page

- Technical light with feel-good guarantee thanks to higher color rendering and two light colors
- Protection class I with integrated overvoltage protection (10,000 V)
- Universal mounting, pole mount/attachment on all pole diameters 42-76mm, swivels /-15°
- Multilayer lens optics with Lumileds® LEDs provide uniform light distribution
- Solid cast aluminum housing similar to RAL 9006 with pressure equalization valve
- Reliable and highly efficient LED driver with a lifetime of > 50,000 h ensures low maintenance
- Easy installation and tool-free maintenance due to disconnect plug
- Power reduction via separately available module (80%, 60%, 40%, 20%)

WEIGHT IN KG	4.88
POWER CONSUMPTION IN WATTS	70
NET LUMINOUS FLUX IN LUMENS	9250
LUMEN PER WATT	132

Dimensions

length: 500mm width: 272mm height: 130mm BEAM ANGLE 155x45°
PROTECTION CLASS (IP) IP66
LIGHT COLOR white

 INPUT VOLTAGE
 186 - 240 AC/DC

 SERVICE LIFE
 approx. 50.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 4000 **COLOR-RENDERING-INDEX** CRI > 82

MAST SUPPORT depending on adapter

 INRUSH CURRENT IN A
 0

 IK PROTECTION
 IK08

 LUMEN PER WATT
 132

 HOUSING COLOUR
 gray

 SUITED FOR EMERGENCY LIGHTING
 yes

OVERVOLTAGE PROTECTION up to 10000 V

WARRANTY IN YEARS

ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION

ACCORDING TO EU REGULATION not required 2019/2015

ETIM GRUPPEN-ID EC000062

MATERIAL COVER Glass transparent

 DIMMING 1-10 V
 Yes

 NO DIM FUNCTION
 Yes

 COLOUR CONSISTENCY (MCADAM ELLIPSE)
 SDCM6

 IMPACT STRENGTH
 IKO8

SUITABLE FOR EMERGENCY LIGHTING YES
PULSE DURATION IN µS 0

BEG FUNDING only relevant in Germany



ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE

Ε