

PRODUCT NO. 5184

DOTLUX Installation frame WINDOW for recessed ceiling mounting 620x620mm LED panels



to the product page

- Bring your ceiling to life with 3-dimensional contours
- Skylight installation frame for 620 mm modular ceilings and 620 mm panels
- Simulates a natural skylight in 3D to create a greater spatial effect
- Compatible with DOTLUX® Skylight motifs
- The LED panel can also be attached to the installation frame with 4 clips
- Installation frame set consisting of 4 plug-in elements

SUCCESSION ARTICLE	-	INSTALLATION DEPTH IN MM	50
WEIGHT IN KG	1.03	INRUSH CURRENT IN A	0
		MATERIAL	Aluminium
		INSTALLATION OPENING WIDTH IN MM	624
		INSTALLATION OPENING LENGHT IN MM	624
Dimensions		SIMILAR TO RAL-COLOUR	9003
		ETIM GRUPPEN-ID	EC000414
length: 632mm		SUITABLE FOR HIGH VOLTAGE LUMINAIRES	Yes
width: 632mm		SUITABLE FOR LAMP POWER IN W	0
height: 50mm		SUITABLE FOR LED LUMINAIRES	Yes
		SUITABLE FOR LOW VOLTAGE LUMINAIRES	Yes
		WITH SPACE FOR GEAR	Yes
		MATERIAL	Aluminium
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany
		APPLICATION	For slab ceiling