

PRODUCT NO. 5198-040110

**DOTLUX LED panel FLATtwice 1200x300mm 40W UGR<19 4000K not dimmable**



to the product page

- Ultra flat pendant luminaire with sturdy, elegant profile housing
- Stylish appearance thanks to screwless design and elegant Y-rope suspension
- Quick installation thanks to magnetic ceiling box
- Direct and indirect light distribution in the ratio 70% DOWN / 30% UP
- Glare-free, homogeneous and shadow-free light distribution / smooth top UGR<19

SUCCESSION ARTICLE	-
WEIGHT IN KG	5.4
POWER CONSUMPTION IN WATTS	40
NET LUMINOUS FLUX IN LUMENS	4200
LUMEN PER WATT	105

Dimensions

length: 1200mm  
width: 300mm  
height: 17mm

BEAM ANGLE	110°
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
LUMEN PER WATT	105
PROTECTION CLASS	I
HOUSING COLOUR	white
GLARE-FREE	UGR < 19
SWITCH CYCLES	> 100.000
SIMILAR TO RAL-COLOUR	9003
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic matt/satinized
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No

<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	E
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No