

PRODUCT NO. 5224

**DOTLUX Installation frame Eco for LED panel 620x620 mm for drywall ceiling kit**



to the product page

- Installation frame for 620mm LED panels in drywall ceilings.
- Frame made of one piece.
- Mounting with 4 spring clips
- Installation opening: 640 x 640mm
- Suitable for drywall ceilings or wooden ceilings with 12.5-25mm thickness

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.88

**Dimensions**

**length:** 664mm  
**width:** 664mm  
**height:** 41mm

INSTALLATION DEPTH IN MM	41
INRUSH CURRENT IN A	0
MATERIAL	Aluminium
INSTALLATION OPENING WIDTH IN MM	624
INSTALLATION OPENING LENGHT IN MM	624
SIMILAR TO RAL-COLOUR	9003
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC000414
SUITABLE FOR HIGH VOLTAGE LUMINAIRES	Yes
SUITABLE FOR LED LUMINAIRES	Yes
SUITABLE FOR LOW VOLTAGE LUMINAIRES	Yes
MATERIAL	Aluminium
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
APPLICATION	For slab ceiling