

PRODUCT NO. 5098

**DOTLUX LED safety light EXITtop with self-test incl. 2 interchangeable lenses white 8h**



to the product page

- Replaceable battery with a lighting duration of 8 hours
- Integrated control LED for operating status
- Only suitable for stand-by mode. If the light is supplied with mains power, the integrated rechargeable battery is charging and the light is in stand-by mode.
- Incl. two easy to change lenses
  - Corridor lighting (asymmetric)
  - wide beam
- Automatic self-test function

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.481
POWER CONSUMPTION IN WATTS	0,7
NET LUMINOUS FLUX IN LUMENS	240

Dimensions

height: 62mm  
diameter: 140mm

BEAM ANGLE	180°
PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	5000
POWER FACTOR	0,3
BATTERY RUNTIME	8h
PROTECTION CLASS	II
HOUSING COLOUR	black
INSTALLATION OPENING DIAMETER IN MM	110-120
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	3
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001957
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
MATERIAL COVER	Other