DOTLUX
LICHT IN BESTER QUALITÄT

PRODUCT NO. 5250

LED-Netzteil CC 5-19W 100-380mA 5-50V dimmbar DALI inkl DC 5,5mm Anschlusskabel





to the product page

WEIGHT IN KG	0.008
POWER CONSUMPTION IN WATTS	3-19
LUMINAIRES PER CIRCUIT BREAKER	B16=50

Dimensions

length: 108mm
width: 52mm
height: 22mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
FREQUENCY RANGE IN HZ	50/60
Output current in A	
POWER FACTOR	0,96
TC TEMPERATURE IN °C	75
PROTECTION CLASS	II
VOLTAGE TYPE	AC/DC
SUITED FOR EMERGENCY LIGHTING	yes
OVERVOLTAGE PROTECTION	1000 V
CORD LENGTH IN M	0.15
OUTPUT VOLTAGE	3 - 50 DC
INPUT VOLTAGE SPAN	110-240 V AC / 176-276 V DC
WARRANTY IN YEARS	2
HOUSING MATERIAL	Plastic
SUITED FOR EMERGENCY POWER	-
INPUT VOLTAGE RANGE LUMINAIRE	110-240 V AC / 176-276 V DC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
DIMMING DALI	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
DIMMING DALI-2	Yes
CORD LENGTH	15 cm