

PRODUCT NO. 5259-030360

DOTLUX LED bollard light WAY 100cm 7.5/15W 3000K



to the product page

Dotlux LED bollard light WAY 100 cm

- Freely selectable light emission area due to interchangeable glass and cover plates
- Power-Select allows the adjustment of the system power 50% / 100%
- High-quality aluminum housing with powder coating in DB703
- Glare-free and homogeneous light distribution with high color rendering $Ra > 82$
- EasyMount platform enables simple and fast installation
- For looping through with connection box (input and output each for $3 \times 2.5 \text{ mm}^2$ cable)
- Mounting base made of special aluminum alloy, approved for installation with ground contact
- Insect-friendly lighting due to warm white LEDs

SUCCESSION ARTICLE	-	BEAM ANGLE	360°
WEIGHT IN KG	4.21	PROTECTION CLASS (IP)	IP65
POWER CONSUMPTION IN WATTS	7.5-15	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	400/800	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	53	SERVICE LIFE	approx. 40.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 82
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK06
		LUMEN PER WATT	53
		PROTECTION CLASS	I
		HOUSING COLOUR	gray
		WARRANTY IN YEARS	5
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC000062
		MATERIAL COVER	Plastic, structured
		NO DIM FUNCTION	Yes
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		IMPACT STRENGTH	IK06
		LAMP TYPE	LED
		PULSE DURATION IN μs	0
		BEG FUNDING	Only relevant in Germany
		ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	G

Dimensions

length: 120mm
width: 120mm
height: 1000mm

diameter: 3mm