

PRODUCT NO. 4468-0FW120-B-Ware

DOTLUX LED-Aufbauleuchte PANELbig 400x400mm 32W COLORselect B-Ware



to the product page

- Eine Artikelnummer - drei Lichtfarben durch COLORselect einstellbar
- Noch schnellere Montage durch speziell entwickelte Grundplatte mit vormontiertem Netzteil
- Massives, pulverbeschichtetes Metallgehäuse
- Größere Lichtfläche durch dünneren Rahmen
- Ermüdungsfreies Arbeiten durch flimmerfreies Licht
- Anschluss über Schnellanschlussklemme
- Geeignet für HCL (HCL-Netzteil und Steuerung notwendig)

SUCCESSION ARTICLE	4468-1FW120
WEIGHT IN KG	2.8
NET LUMINOUS FLUX IN LUMENS	max. 2500
POWER CONSUMPTION IN WATTS	max. 32
CONSUMPTION (KWH/1000H)	max. 32
LUMEN PER WATT	78

Dimensions

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP40
LIGHT COLOR	multicoloured
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
POWER SUPPLY	Separate, enclosed
COLOR-RENDERING-INDEX	CRI > 92
POWER FACTOR	0,95
SPECIAL FEATURE	Flicker-free
LUMEN PER WATT	78
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
SWITCH CYCLES	> 100.000
FOOD-READY	Yes
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	0
HOUSING MATERIAL	Aluminium
L/B VALUE	L80/B10
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ASSORTMENT	Highline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No

DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
OPTICS OF THE COVER	frosted
CORD LENGTH	30 cm