

PRODUCT NO. 5274

DOTLUX DMX receiver/dimmer with integrated stand alone function 4 channels 12-24V DC 4x5A  
DIN rail



to the product page

- Digital numerical display, DMX start address setting via buttons.
- Flexible input voltage 12-24V with screw terminal.
- RDM function can realize communication between DMX master and decoder.
- DMX preset for 1/2 or 4color stripes.
- More suitable for video recording by adjustable PWM frequency 2000/500Hz
- More beautiful dimming effects by adjustable dimming curve (Logarithmic or Linear)
- Stand-alone mode for RGB/RGBW and 4-channel dimmer. Built-in programs instead of DMX signal
- Suitable for single color, dual color, RGB or RGBW constant voltage LED strips or modules
- Built-in protection circuit (overload, overheat, short circuit)

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.12	INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	85
		COLOUR CHANNELS	RGBW
		OUTPUT VOLTAGE	12 - 24 DC
		WARRANTY IN YEARS	3
		CONTROL METHOD	DMX
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002924
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany
Dimensions			
length: 115mm			
width: 48mm			
height: 67mm			