

PRODUCT NO. 5275

DOTLUX DMX receiver/dimmer with integrated stand alone function 4 channels 12-24V DC 4x5A



to the product page

- Digital numerical display, DMX start address setting via buttons.
- Flexible input voltage 12-24V with screw terminal.
- RDM function can realize communication between DMX master and decoder.
- DMX preset for 1/2 or 4color stripes.
- More suitable for video recording by adjustable PWM frequency 2000/500Hz
- More beautiful dimming effects by adjustable dimming curve (Logarithmic or Linear)
- Stand-alone mode for RGB/RGBW and 4-channel dimmer. Built-in programs instead of DMX signal
- Suitable for single color, dual color, RGB or RGBW constant voltage LED strips or modules
- Built-in protection circuit (overload, overheat, short circuit)

| | | | |
|--------------------|-------|-----------------------|--------------------------|
| SUCCESSION ARTICLE | - | PROTECTION CLASS (IP) | IP20 |
| WEIGHT IN KG | 0.112 | OUTPUT VOLTAGE | 12 - 24 DC |
| | | WARRANTY IN YEARS | 3 |
| | | CONTROL METHOD | DMX |
| | | ETIM GRUPPEN-ID | EC002924 |
| | | BEG FUNDING | Only relevant in Germany |

Dimensions

width: 50mm

height: 23mm

length: 170mm