

PRODUCT NO. 5297-098060

DOTLUX Wall lamp BRICK 15W COLORselect black



to the product page

- Particularly soft light effect due to internal reflector creates great atmosphere
- Robust, splash-proof housing made of aluminum and real glass offers with IP65 best protection for outdoor use
- Phase-section dimmable and therefore also suitable for indoor use as a modern wall light
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal block
- EasyBase platform enables simple and fast mounting
- Mounting also possible vertically

SUCCESSION ARTICLE	-	BEAM ANGLE	60° x 115° x 40°
WEIGHT IN KG	1.13	PROTECTION CLASS (IP)	IP65
LUMEN PER WATT	73	LIGHT COLOR	multicoloured
POWER CONSUMPTION IN WATTS	15	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	1100	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000/3500/4000
		POWER FACTOR	0,9
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK00
		LUMEN PER WATT	73
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	black
		SUITED FOR EMERGENCY LIGHTING	No
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	3
		SIMILAR TO RAL-COLOUR	9005
		SUITABLE FOR SURFACE MOUNTING	Yes
		SUITABLE FOR MOUNTING	No
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		WITH ILLUMINANT	No
		SUITABLE FOR WALL MOUNTING	Yes
		SUITABLE FOR SUSPENDED MOUNTING	No
		SUITABLE FOR CEILING MOUNTING	No

Dimensions

height: 60mm
length: 300mm
width: 100mm

SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
LAMP HOLDER	-
MATERIAL COVER	Glass matt/satinized
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	Yes
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	Yes
DIMMING PHASE CUT-OFF	Yes
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	Yes
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	2
IMPACT STRENGTH	IK00
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	750 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Ending
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0
COLOUR OF LIGHT ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	15
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No

DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
TYPE OF GRID	Matt
LIGHT OUTLET	Indirect
SURFACE PROTECTION HOUSING	Powder coating
LIGHT SHARING	Double asymmetric
LIGHT DISTRIBUTOR	Other
TYPE OF CONTROL GEAR	Not required
BEAM ANGLE	Open beam/diffuse
CONNECTION TYPE	Other