

PRODUCT NO. 5300-030030

DOTLUX Wall lamp FLASK 6W 3000K white













to the product page

- Decorative, flat wall lamp with glare-free light for stair and path lighting
- Particularly insect-friendly lighting due to warm white LEDs and asymmetrical light distribution
- Robust, splash-proof housing made of aluminum offers with IP65 best protection for outdoor
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal block
- Sustainable product design with easily replaceable components
- EasyBase platform enables simple and fast mounting

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.47
POWER CONSUMPTION IN WATTS	6
LUMEN PER WATT	88
NET LUMINOUS FLUX IN LUMENS	530

Dimensions

length: 135mm width: 90mm

height: 31mm

BEAM ANGLE	29° x 77° x 8°
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
POWER FACTOR	0,83
INRUSH CURRENT IN A	0
IK PROTECTION	IK08
LUMEN PER WATT	88
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	3
SIMILAR TO RAL-COLOUR	9016
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No

No

No

No

No

DIMMING DSI

(INTEGRATED)
DIMMING LINESWITCH

DIMMING POTENTIOMETER

DIMMING MANUFACTURER'S

PROPRIETARY SYSTEM



DIMMING MAINS VOLTAGE No MODULATION DIMMING PHASE CUT-OFF No **DIMMING PROGRAMMABLE** No DIMMING RF No DIMMING SINE WAVE REDUCTION No DIMMING TOUCH AND DIM No DIMMING ZIGBEE No DIMMING WITH PUSH-BUTTON No DIMMING DEPENDING ON CONTROL No **GEAR** NO DIM FUNCTION Yes **COLOUR CONSISTENCY (MCADAM** SDCM6 ELLIPSE) IK08 IMPACT STRENGTH **DIMMING DALI-2** No DIMMING PHASE CUT-ON No **DIMMING GPRS** No PULSE DURATION IN µS 0 **BEG FUNDING** Only relevant in Germany ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE F **COLOUR OF LIGHT ADJUSTABLE** No