

PRODUCT NO. 5301-030030

DOTLUX Wall lamp FLASK 10W 3000K white







to the product page

- Decorative, flat wall light with glare-free light for stair and path lighting
- Particularly insect-friendly lighting due to warm white LEDs and asymmetrical light distribution
- Robust, splash-proof housing made of aluminum offers with IP65 best protection for outdoor use
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal block
- Sustainable product design with easily replaceable components
- EasyBase platform enables simple and fast mounting

SUCCESSION ARTICLE	-	BEAM ANGLE	29° x 77° x 8°
		PROTECTION CLASS (IP)	IP65
WEIGHT IN KG	0.6	LIGHT COLOR	white
LUMEN PER WATT	94	INPUT VOLTAGE	220 - 240 V AC
POWER CONSUMPTION IN WATTS	10	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	940	COLOR TEMPERATURE IN KELVIN	3000
		POWER FACTOR	0,83
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK08
Dimensions		LUMEN PER WATT	94
		HOUSING COLOUR	white
width: 90mm		SWITCH CYCLES	> 100.000
height: 31mm		WARRANTY IN YEARS	3
length: 175mm		SIMILAR TO RAL-COLOUR	9016
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Plastic, transparent
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No

DIMMING LINESWITCH

No



DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
NO DIM FUNCTION COLOUR CONSISTENCY (MCADAM ELLIPSE)	Yes SDCM6
COLOUR CONSISTENCY (MCADAM	
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COLOUR CONSISTENCY (MCADAM ELLIPSE) IMPACT STRENGTH	SDCM6
COLOUR CONSISTENCY (MCADAM ELLIPSE) IMPACT STRENGTH DIMMING DALI-2	SDCM6 IKO8 No
COLOUR CONSISTENCY (MCADAM ELLIPSE) IMPACT STRENGTH DIMMING DALI-2 DIMMING PHASE CUT-ON	SDCM6 IK08 No No
COLOUR CONSISTENCY (MCADAM ELLIPSE) IMPACT STRENGTH DIMMING DALI-2 DIMMING PHASE CUT-ON DIMMING GPRS	SDCM6 IKD8 No No No
COLOUR CONSISTENCY (MCADAM ELLIPSE) IMPACT STRENGTH DIMMING DALI-2 DIMMING PHASE CUT-ON DIMMING GPRS PULSE DURATION IN µS	SDCM6 IKO8 No No No O
COLOUR CONSISTENCY (MCADAM ELLIPSE) IMPACT STRENGTH DIMMING DALI-2 DIMMING PHASE CUT-ON DIMMING GPRS PULSE DURATION IN µS BEG FUNDING ENERGIEEFFIZIENZKLASSE DER	SDCM6 IK08 No No O Only relevant in Germany