

PRODUCT NO. 5302-030060

DOTLUX Wall lamp GUIDERound 5W 3000K



to the product page

- Decorative, flat wall lamp with glare-free light for stair and path lighting
- Particularly insect-friendly lighting due to warm white LEDs and asymmetrical light distribution
- Robust, splash-proof housing made of aluminum offers with IP65 best protection for outdoor use
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal block
- Sustainable product design with easily replaceable components
- EasyBase platform enables simple and fast mounting

| | |
|-----------------------------|------|
| SUCCESSION ARTICLE | - |
| WEIGHT IN KG | 0.33 |
| POWER CONSUMPTION IN WATTS | 5 |
| NET LUMINOUS FLUX IN LUMENS | 130 |
| LUMEN PER WATT | 26 |

Dimensions

diameter: 114mm
height: 37mm

| | |
|--|--------------------------|
| BEAM ANGLE | 60° |
| PROTECTION CLASS (IP) | IP65 |
| LIGHT COLOR | white |
| INPUT VOLTAGE | 220 - 240 V AC |
| SERVICE LIFE | approx. 50.000 h at 25°C |
| COLOR TEMPERATURE IN KELVIN | 3000 |
| COLOR-RENDERING-INDEX | CRI > 82 |
| POWER FACTOR | 0,9 |
| INRUSH CURRENT IN A | 0 |
| IK PROTECTION | IK08 |
| LUMEN PER WATT | 26 |
| PROTECTION CLASS | I |
| HOUSING COLOUR | black |
| WARRANTY IN YEARS | 3 |
| SIMILAR TO RAL-COLOUR | 9005 |
| ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| ETIM GRUPPEN-ID | EC002892 |
| MATERIAL COVER | Glass transparent |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | No |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |

| | |
|---|--------------------------|
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| DIMMING DEPENDING ON CONTROL GEAR | No |
| NO DIM FUNCTION | Yes |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM6 |
| IMPACT STRENGTH | IK08 |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| PULSE DURATION IN µS | 0 |
| BEG FUNDING | Only relevant in Germany |
| ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE | F |
| COLOUR OF LIGHT ADJUSTABLE | No |