

PRODUCT NO. 5303-030070

DOTLUX Wall lamp GUIDERound 8W 3000K



to the product page

- Decorative, flat wall lamp with glare-free light for stair and path lighting
- Particularly insect-friendly lighting due to warm white LEDs and asymmetrical light distribution
- Robust, splash-proof housing made of aluminum offers with IP65 best protection for outdoor use
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal block
- Sustainable product design with easily replaceable components
- EasyBase platform enables simple and fast mounting

SUCCESSION ARTICLE	-	BEAM ANGLE	70°
WEIGHT IN KG	0.62	PROTECTION CLASS (IP)	IP65
NET LUMINOUS FLUX IN LUMENS	240	LIGHT COLOR	white
LUMEN PER WATT	30	INPUT VOLTAGE	220 - 240 V AC
POWER CONSUMPTION IN WATTS	8	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,9
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK08
		LUMEN PER WATT	30
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	black
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	3
		SIMILAR TO RAL-COLOUR	9005
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Glass transparent
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No

Dimensions

diameter: 180mm
height: 35mm

DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	F
COLOUR OF LIGHT ADJUSTABLE	No