

PRODUCT NO. 5307-030100

DOTLUX Wall lamp FLEXOtwIn 16W 3000K



to the product page

- Modern decorative wall light shining on both sides
- Variable lighting effects due to pluggable internal stencils
- Robust, splash-proof housing made of aluminum offers the best protection for outdoor use with IP65
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal block
- EasyBase platform enables simple and fast mounting
- Luminaire can be mounted to shine upwards or downwards
- Insect-friendly lighting thanks to warm white LEDs

SUCCESSION ARTICLE	-	BEAM ANGLE	100°
WEIGHT IN KG	0.77	PROTECTION CLASS (IP)	IP65
POWER CONSUMPTION IN WATTS	16	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	1250	INPUT VOLTAGE	220 - 240 V AC
LUMEN PER WATT	78	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,9
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK06
		LUMEN PER WATT	78
		PROTECTION CLASS	I
		HOUSING COLOUR	black
		WARRANTY IN YEARS	3
		SIMILAR TO RAL-COLOUR	9005
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Glass transparent
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No

Dimensions

length: 165mm
width: 95mm
height: 67mm

DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	F
COLOUR OF LIGHT ADJUSTABLE	No