

PRODUCT NO. 5308-030100

DOTLUX Wall lamp FLEXOtwin-sensor 16W 3000K



to the product page

- Modern decorative sensor wall light shining on both sides
- Integrated PIR sensor with adjustable light duration and brightness level
- Variable lighting effects due to pluggable internal stencils
- Robust, splash-proof housing made of aluminum offers with IP65 best protection for outdoor use
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal block
- EasyBase platform enables simple and quick installation
- Insect-friendly lighting thanks to warm white LEDs

WEIGHT IN KG	0.79
LUMEN PER WATT	78
POWER CONSUMPTION IN WATTS	16
NET LUMINOUS FLUX IN LUMENS	1250

Dimensions

width: 95mm
height: 67mm
length: 165mm

BEAM ANGLE	100°
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
IK PROTECTION	IK06
LUMEN PER WATT	78
PROTECTION CLASS	I
HOUSING COLOUR	black
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	3
SIMILAR TO RAL-COLOUR	9005
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Glass transparent
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No

DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	F
COLOUR OF LIGHT ADJUSTABLE	No