

PRODUCT NO. 2827-299120

## DOTLUX LED downlight CIRCLE 18W COLORselect 500mA 4pin



to the product page

\ "COLORselect" \": 3 light colors in one luminaire. For every application environment the right light color can be set:

1. Warm white 3,000 K: Hotel, store, wellness/spa areas, home & living.
2. Neutral white 4,000 K: Office, gastronomy, industry, sanitary, retirement homes and hospitals
3. Daylight white 5,700 K: Industry, conference rooms, educational institutions, office

- \ "HCL READY" \": This article is suitable for use as HCL (Human Centric Lighting) Lighting (additional components are required). Human Centric Lighting is the most natural form of artificial light, because it replicates the sun's course of the day. By adapting the lighting to the human biorhythm, well-being and performance can be increased.
- Stable light output thanks to oversized die-cast aluminum heat sink and SAMSUNG® LED (LM80 certified) on aluminum core board
- Natural color perception thanks to extra high CRI value
- Fast exchange of power supplies due to lockable connector
- High compatibility with various LED power supplies
- Sturdy mounting brackets ensure a secure hold
- Extra flat design allows use even in difficult mounting locations
- This light can be upgraded for use as emergency lighting. (The battery kit accessories are required)

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	120°
<b>PREDECESSOR ARTICLE</b>	2827-1FW120 2827-0FW120	<b>PROTECTION CLASS (IP)</b>	other Front IP54 / rear IP20
<b>WEIGHT IN KG</b>	0.7	<b>LIGHT COLOR</b>	white
<b>POWER CONSUMPTION IN WATTS</b>	18	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>NET LUMINOUS FLUX IN LUMENS</b>	max. 1950	<b>COLOR TEMPERATURE IN KELVIN</b>	3000/4000/5700
<b>LUMEN PER WATT</b>	max. 108	<b>COLOR-RENDERING-INDEX</b>	CRI > 92
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK06
		<b>LUMEN PER WATT</b>	max. 108
		<b>PROTECTION CLASS</b>	III
		<b>HOUSING COLOUR</b>	white
		<b>SWITCH CYCLES</b>	> 100.000
		<b>FOOD-READY</b>	Yes
		<b>INSTALLATION OPENING DIAMETER IN MM</b>	160-185
		<b>WARRANTY IN YEARS</b>	7
		<b>L80/B10</b>	50000
		<b>SIMILAR TO RAL-COLOUR</b>	9003
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required

### Dimensions

**diameter:** 195mm

**height:** 59mm

LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC001744
MATERIAL COVER	Plastic matt/satinized
DIMMING DEPENDING ON CONTROL GEAR	Yes
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
COLOUR OF LIGHT ADJUSTABLE	Positions
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µs	0
LIFETIME L90/B50 AT 25°C	33333
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-