

PRODUCT NO. 4864-050120-B-Ware

DOTLUX LED-Fluter LENSplus 50W 5000K 120° Abstrahlwinkel B-Ware



to the product page

Große Vielfalt an verschiedenen Abstrahlwinkeln ermöglicht für jede Situation eine optimale Ausleuchtung

- Zuverlässiger Betrieb durch hocheffiziente Lumileds®-LEDs mit 3-Step MacAdam-Binning
- Massives, wasserfestes, ADC12-Aluminium-Druckgussgehäuse mit Druckausgleichsventil (IP 66/IK08) und hochwertiger Pulverbeschichtung von Akzo Nobel
- ESG-Glas "ULTRA CLEAR" hochtransparentes Glas für ausgezeichnete Lichtfarbe und verbesserte Lichtausbeute
- Langlebige Industrienetzteile mit 10kV Überspannungsschutz
- Gebogener Montagebügel ermöglicht einfachste Montage ohne den Bügel demontieren zu müssen (frei drehbar 320°)
- Inkl. 1,5m UV-Stabiles Gummikabel (H05RN-F offene Enden)
- Austauschbare Komponenten dadurch reparaturfähig
- Nachhaltiges, reparaturfähiges Produktdesign

PREDECESSOR ARTICLE	3016-155120K	BEAM ANGLE	120°
WEIGHT IN KG	2.1	PROTECTION CLASS (IP)	IP66
POWER CONSUMPTION IN WATTS	50	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	6100	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	122	COLOR TEMPERATURE IN KELVIN	5000
		COLOR-RENDERING-INDEX	CRI > 82
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK08
		LUMEN PER WATT	122
Dimensions		PROTECTION CLASS	I
		HOUSING COLOUR	black
		SWITCH CYCLES	> 100.000
		OVERVOLTAGE PROTECTION	up to 6000 V
		INPUT VOLTAGE SPAN	220-240 V AC
		WARRANTY IN YEARS	0
		INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
		ETIM GRUPPEN-ID	EC001744
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No

DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK08
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0