

PRODUCT NO. 4338-299160

DOTLUX LED luminaire LUNAsilver-pioneer Ø490mm 18W 6W COLORselect



to the product page

- innovative luminaire technology for many different application scenarios
e.g. retirement homes, parking garages, hospitals, supermarkets, hotels, etc.
- Luminaire with three independent light circuits (18W - 18W - 6W)
- light circuits can be flexibly combined with each other
- each circuit can be set to three different color temperatures
- many different light scenarios possible
- economical 6W circuit for ambient or emergency lighting
- extended range of functions by optional accessories:
e.g. sensor, changeover switch or emergency power accukit
- sustainable, repairable product design

SUCCESSION ARTICLE	4338-399120
PREDECESSOR ARTICLE	4338-1FW160
WEIGHT IN KG	1.73
LUMEN PER WATT	76
POWER CONSUMPTION IN WATTS	18W+18W+6W
NET LUMINOUS FLUX IN LUMENS	max.3200

Dimensions

height: 120mm
diameter: 490mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP44
LIGHT COLOR	multicoloured
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,6
INRUSH CURRENT IN A	0
LUMEN PER WATT	76
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	yes
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	5
RATED CURRENT	0,08
SUITABLE FOR SURFACE MOUNTING	Yes
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes

SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
MATERIAL COVER	Plastic, opal
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
SUITABLE FOR EMERGENCY LIGHTING	Yes
WITH MOVEMENT SENSOR	No
WITH AIR SLOTS	No
CONSTANT LIGHT OUTPUT (CLO)	Yes
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COLOUR OF LIGHT ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	46
LAMP TYPE	LED exchangeable
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E
TYPE OF CONTROL GEAR	Electronic transformer
LIGHT OUTLET	Direct
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric

SURFACE PROTECTION HOUSING

Powder coating

TYPE OF GRID

None

LIGHT DISTRIBUTOR

None

BEAM ANGLE

Extreme wide beam >80°