

PRODUCT NO. 3024-240120

DOTLUX LED downlight CIRCLEflat 18W 4000K incl. driver



to the product page

- Flat design with integrated power supply enables use even in difficult installation locations
- Backlight technology with robust aluminum core board and good thermal management
- Wide housing rebate covers inaccurately cut mounting hole
- Plastic-sheathed metal clips provide secure hold

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3024-040120 2825 3024-0FW120 3024-140120
WEIGHT IN KG	0.19
POWER CONSUMPTION IN WATTS	18
NET LUMINOUS FLUX IN LUMENS	1300
LUMEN PER WATT	72

Dimensions

diameter: 222mm
height: 28mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 30.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,76
INRUSH CURRENT IN A	0
IK PROTECTION	IK03
LUMEN PER WATT	72
PROTECTION CLASS	II
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	No
SWITCH CYCLES	> 60.000
INSTALLATION OPENING WIDTH IN MM	0
INSTALLATION OPENING DIAMETER IN MM	187-200
INSTALLATION OPENING LENGHT IN MM	0
WARRANTY IN YEARS	2
L80/B10	80000
RATED CURRENT	0.1
SUITABLE FOR SURFACE MOUNTING	Yes
SUITABLE FOR MOUNTING	Yes
DIMMING WITHOUT DIMMER	No

ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	80000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	30000
LIFETIME L80/B20 AT 25°C	0
ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
LAMP HOLDER	-
MATERIAL COVER	-
TYPE OF CONTROL GEAR	LED operating device current- controlled
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK03
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG2
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No

COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	Yes
SUITABLE FOR LIGHT-TRACK MOUNTING	No
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	17.7
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	30000
LIFETIME L90/B10 AT 25°C	7500
PULSE DURATION IN µS	0
LIFETIME L90/B50 AT 25°C	10000
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	G
LIGHT SHARING	Asymmetric
LIGHT OUTLET	Direct
TYPE OF WIRING	Suitable for through wiring
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
SURFACE PROTECTION	Plastic-coated
ADJUSTABILITY	Not adjustable
LIGHT DISTRIBUTOR	Other
REFLECTOR	None
BEAM ANGLE	Extreme wide beam >80°
DEGREE OF PROTECTION (NEMA)	Other
CONNECTION TYPE	Other