

PRODUCT NO. 5068-1

LED power supply CC 15-44W 300-1050mA 6-52V PUSH dimmable DALI-2 suitable for central battery through-wireable



to the product page

- The power supply is dimmable via DALI-2
- With the constant current technology (CC) it is suitable for luminaires with constant current
- The connected constant current luminaires can be dimmed between 1%-100%
- The output current is adjustable:
300/350/400/450/500/550/600/650/700/750/800/850/900/950/1000/1050mA
- The power supply is set to 950mA by default
- Suitable for use in emergency lighting systems

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	5068
WEIGHT IN KG	0.214
POWER CONSUMPTION IN WATTS	15-44W

Dimensions

length: 212mm
width: 57mm
height: 30mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 100.000 h bei Tc,max = 75°C
OUTPUT CURRENT IN A	0,35-1,05
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	90
PROTECTION CLASS	II
OUTPUT VOLTAGE	6-52
INPUT VOLTAGE SPAN	176-264 V AC / 170-275 V DC
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	176-264 V AC / 170-275 V DC
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	Yes
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	Yes
NO DIM FUNCTION	No
CONSTANT LIGHT OUTPUT (CLO)	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR DC-VOLTAGE (PRIMARY SIDE)	No
SUITABLE FOR CONSTANT CURRENT	Yes
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany