

PRODUCT NO. 5353-050360

## DOTLUX Construction site floodlight WORKERrocket 70W 5000K CRI>92 IP54 IK07



to the product page

- Easy to transport thanks to compact design and an ergonomic carrying handle
- High stability thanks to integrated tripod guarantees safe work
- 2 m flexible H07RNF - rubber cable for optimal use on the construction site or outdoors
- Integrated cable holder
- Additional socket IP 54 maximum 1800 Watt / 230 Volt / 16A
- Glare-free all-round lighting with 360° beam angle
- Most natural color rendering CRI >92 for demanding users
- Splash-proof housing IP 54

SUCCESSION ARTICLE 5353-150360

WEIGHT IN KG 4.1

LUMEN PER WATT 86

POWER CONSUMPTION IN WATTS 70

NET LUMINOUS FLUX IN LUMENS 6000

### Dimensions

height: 1352mm

length: 805mm

width: 636mm

BEAM ANGLE	360°
PROTECTION CLASS (IP)	IP54
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 30.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	5000
COLOR-RENDERING-INDEX	CRI > 92
INRUSH CURRENT IN A	0
IK PROTECTION	IK07
LUMEN PER WATT	86
PROTECTION CLASS	I
HOUSING COLOUR	multicoloured
WARRANTY IN YEARS	2
L80/B10	22500
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
MOUNTING LOCATION	Indoor + covered outdoor
LIFETIME L80/B10 AT 25°C	22500
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	45000
ETIM GRUPPEN-ID	EC000346
WITH ILLUMINANT	Yes
IMPACT STRENGTH	IK07
SUITABLE FOR LAMP POWER IN W	63.5
LIFETIME L70/B50 AT 25°C	45000
LIFETIME L90/B10 AT 25°C	11250
PULSE DURATION IN µS	0

LIFETIME L90/B50 AT 25°C	15000
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
LAMP TYPE	Other
CONNECTION TYPE	Other