


PRODUCT NO. 3292-240060-B-Ware

DOTLUX LED-Leuchteneinsatz LINEAselect 1437mm 25-75W 4000K dimmbar 1-10V 60°



to the product page

- Quick-release fasteners for all connections
- Tool-free mounting rail with integrated through-wiring
- Lamp insert with flexible phase selection and power adjustment
- Optimized transmittance of the diffusing lens
- Self-cooling LED module
- High luminous efficacy thanks to optimized profile design
- Easily replaceable light units with excellent price/performance ratio
- Long life thanks to oversized cooling system
- Suitable for central battery

WEIGHT IN KG	1.9
NET LUMINOUS FLUX IN LUMENS	max. 11680
LUMEN PER WATT	max. 160
POWER CONSUMPTION IN WATTS	25-75

Dimensions

BEAM ANGLE	60°
PROTECTION CLASS (IP)	IP40
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
FREQUENCY RANGE IN HZ	50/60
POWER SUPPLY	Integrated
COLOR-RENDERING-INDEX	CRI > 83
POWER FACTOR	0,95
LUMEN PER WATT	max. 160
PROTECTION CLASS	I
SUITED FOR EMERGENCY LIGHTING	yes
FIRE PROTECTION "D"	yes
SWITCH CYCLES	> 100.000
COVER MATERIAL	PMMA
WARRANTY IN YEARS	0
SUITED FOR EMERGENCY POWER	-
ASSORTMENT	Proline
ETIM GRUPPEN-ID	EC002892
DIMMING 1-10 V	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
LIGHT COLOUR ACCORDING TO EN 12464-1	neutral white 3300 to 5300 K