


PRODUCT NO. 5369-050090

DOTLUX LED indoor floodlight LIGHTSHOWERSmart Max.150W 5000K Power Select



to the product page

- Glare-reduced hall spotlight thanks to ring lens
- Additional savings potential due to optional retrofittable daylight/motion sensors, programmable via infrared remote control
- POWERselect in combination with sensors - adjustable directly at the device (50%, 60%, 75%, 100%)
- 1-10V dimmable, with optional converter Art.5078 also DALI-capable
- Optimal light output even in high altitudes due to already installed 90° ring lens
- Corrosion protected by powder-coated, robust aluminum housing IP65/IK08
- D-certified for use in fire hazardous locations suitable according to DIN EN 60598-2-24, VDE 0711-2-24
- Suitable for use in food processing plants (IFS and BRC)
- Sustainable product design due to easily replaceable components

SUCCESSION ARTICLE 5369-250105
PREDECESSOR ARTICLE 4898-040090

WEIGHT IN KG 2.25
POWER CONSUMPTION IN WATTS 150W
NET LUMINOUS FLUX IN LUMENS 24700

Dimensions

height: 184mm
diameter: 271mm

BEAM ANGLE 90°
PROTECTION CLASS (IP) IP65
INPUT VOLTAGE 220 - 240 V AC
SERVICE LIFE ca. 74.000 h bei 25°C
COLOR TEMPERATURE IN KELVIN 5000
COLOR-RENDERING-INDEX CRI > 82
POWER FACTOR 0,9
INRUSH CURRENT IN A 0
IK PROTECTION IK08
PROTECTION CLASS I
HOUSING COLOUR black
FOOD-READY Yes
WARRANTY IN YEARS 5
L80/B10 73000
ASSORTMENT Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 not required
LIFETIME L80/B10 AT 25°C 73000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C 129000
ETIM GRUPPEN-ID EC001744
DIMMING 1-10 V Yes
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM Yes
DIMMING RF Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE) SDCM6

IMPACT STRENGTH
LUMINOUS FLUX ADJUSTABLE
LIFETIME L70/B50 AT 25°C
LIFETIME L90/B10 AT 25°C
PULSE DURATION IN µS
BEG FUNDING

IK08
Positions
129000
32250
0
only relevant in Germany