

PRODUCT NO. 900049

DOTLUX LED-Leuchte DISCugr Ø400mm 40W COLORselect und POWERselect DALI



to the product page

- Flexible use as desired: available as ceiling, wall, surface-mounted or pendant luminaire in 3 sizes (400,600,800mm)
- Glare-free working thanks to microprismatic diffuser UGR<19 (suitable for computer workstations)
- Modern powder-coated aluminium housing (black - similar to RAL9005) with stepped luminaire housing 55mm high
- Easy and quick installation via EASYbase platform
- Individually adjustable for a variety of applications thanks to COLORselect technology
- Adjustable output with POWERselect (47W / 55W / 68W / 75W)
- Pleasant feeling of space due to indirect light component
- Sustainable product design thanks to interchangeable components

SUCCESSION ARTICLE	Kein Nachfolger - Abverkauf Sonderartikel	PROTECTION CLASS (IP)	IP40
WEIGHT IN KG	3.475	LIGHT COLOR	multicoloured
LUMEN PER WATT	105	SERVICE LIFE	approx. 50.000 h at 25°C
POWER CONSUMPTION IN WATTS	35-40	COLOR TEMPERATURE IN KELVIN	3000/3500/4000
NET LUMINOUS FLUX IN LUMENS	3500-4300	FREQUENCY RANGE IN HZ	50/60
		COLOR-RENDERING-INDEX	CRI > 82
		LUMEN PER WATT	105
		PROTECTION CLASS	I
		HOUSING COLOUR	black
		SWITCH CYCLES	> 100.000
		INPUT VOLTAGE SPAN	220-240 V AC
		SIMILAR TO RAL-COLOUR	9005
		INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No

Dimensions

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	No
DIMMING DALI-2	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIGHT COLOUR ACCORDING TO EN 12464-1	warm white <3300 K