

PRODUCT NO. 4736-040120-B-Ware

DOTLUX LED Anbauleuchte QUADGUARDdali 650x650mm 200W 4000K DALI B-Ware



to the product page

- Particularly easy on the eyes due to 9 times larger illuminated surface than conventional hall floodlights, therefore also ideal for ball sports.
- Extremely uniform illumination due to diffuse light, glare limitation UGR typically <23
- Ball impact certified, solid housing with satinised toughened safety glass cover "ULTRA CLEAR SATINATO
- Certified for various mounting methods (Fix mounting bracket, suspension lugs)
- Fatigue-free, flicker-free light guarantees high-quality HD video recordings
- Pre-mounted Stucchi quick connector (connection socket included)
- The pressure equalisation valve increases the service life of the seals and prevents condensation in the luminaire
- Suitable for central battery (also available as single battery version)
- Sustainable, repairable product design MADE IN EUROPE
- Silicone-free construction for sensitive production areas
- DALI dimmable version

WEIGHT IN KG	13.6
NET LUMINOUS FLUX IN LUMENS	24500
LUMEN PER WATT	123
POWER CONSUMPTION IN WATTS	200

Dimensions

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP65
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,98
INRUSH CURRENT IN A	0
IK PROTECTION	IK10
LUMEN PER WATT	123
PROTECTION CLASS	I
HOUSING COLOUR	white
BALLPROOF	yes
WARRANTY IN YEARS	0
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
IMPACT STRENGTH	IK10
DIMMING DALI-2	Yes
PULSE DURATION IN µS	0