

PRODUCT NO. 600095

**DOTLUX LED downlight CIRCLEflat 6W 3000K incl. driver bundle 5 pcs.**



to the product page

- Flat design with integrated power supply enables use even in difficult installation locations
- Backlight technology with robust aluminum core board and good thermal management
- Wide housing rebate covers inaccurately cut mounting hole
- Plastic coated metal clips provide secure hold
- 25mm mounting depth
- Set of 5

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3022-040120 2823 3022-0FW120
WEIGHT IN KG	0.3
LUMEN PER WATT	65
NET LUMINOUS FLUX IN LUMENS	390
POWER CONSUMPTION IN WATTS	6

Dimensions

height: 26mm  
diameter: 118mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 30.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,6
LUMEN PER WATT	65
PROTECTION CLASS	II
HOUSING COLOUR	white
SWITCH CYCLES	> 100.000
INSTALLATION OPENING DIAMETER IN MM	95-100
WARRANTY IN YEARS	2
ASSORTMENT	Ecoline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
MATERIAL COVER	Plastic matt/satinized
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No

<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	G
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No