

PRODUCT NO. 5389

DOTLUX LED rescue light EXIT 3,8W 6000K incl. 4 pictograms 3h operation,(continuous operation or emergency lighting) Li-FEPO4 autom. self test



to the product page

- \"ONE FOR ALL\" One order number for all arrow directions.
- Splash-proof housing (IP65) made of shatterproof polycarbonate
- Replaceable LiFePO4 battery guarantees a light duration of 3 hours
- Different switching programs selectable: continuous or stand-by switching
- Integrated control LED for operating status
- Power consumption in standby mode less than 0.5 Watt
- Automatic self-test function
- Including 4 self-adhesive standard pictograms (left ,right, top, bottom)

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3363, 3009-160180
WEIGHT IN KG	0.61
POWER CONSUMPTION IN WATTS	3,8
NET LUMINOUS FLUX IN LUMENS	AC 380 / Akku 240
LUMEN PER WATT	100

Dimensions

length: 349mm
width: 107mm
height: 64mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP65
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
OUTPUT LUMEN DURING EMERGENCY	220
RANGE OF SENSOR	20
COLOR TEMPERATURE IN KELVIN	6000-7000
COLOR-RENDERING-INDEX	CRI > 70
POWER FACTOR	0,45
IK PROTECTION	IK08
BATTERY RUNTIME	3h
LUMEN PER WATT	100
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
PICTOGRAM INCLUDED	Yes
L80/B10	50000
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC001957
WITH ILLUMINANT	Yes
IMPACT STRENGTH	IK08
CONSTANT LIGHT OUTPUT (CLO)	Yes

MOUNTING METHOD	Ceiling mounting
WITH REMOTE CONTROL	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
LIFETIME L90/B50 AT 25°C	33333
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
MATERIAL COVER	Other