

PRODUCT NO. 600096

DOTLUX LED downlight CIRCLEflat 6W 4000K incl. driver bundle 5 pcs.















to the product page

V AC

- Flat design with integrated power supply enables use even in difficult installation locations
- Backlight technology in robust design
- Stable mounting brackets provide a secure hold
- Set of 5

| SUCCESSION ARTICLE | - | BEAM ANGLE | 120° |
|-----------------------------|------------------------------|--|-------------|
| PREDECESSOR ARTICLE | 3022-040120 2823 3022-0FW120 | PROTECTION CLASS (IP) | IP20 |
| | | LIGHT COLOR | white |
| WEIGHT IN KG | 0.33 | INPUT VOLTAGE | 220 - 240 \ |
| LUMEN PER WATT | 65 | SERVICE LIFE | approx. 30. |
| POWER CONSUMPTION IN WATTS | 6 | COLOR TEMPERATURE IN KELVIN | 4000 |
| NET LUMINOUS FLUX IN LUMENS | 390 | COLOR-RENDERING-INDEX | CRI > 82 |
| | | POWER FACTOR | 0,6 |
| | | LUMEN PER WATT | 65 |
| | | PROTECTION CLASS | II |
| Dimensions | | HOUSING COLOUR | white |
| | | SWITCH CYCLES | > 60.000 |
| height: 26mm | | INSTALLATION OPENING DIAMETER IN MM | 95-100 |
| diameter: 118mm | | WARRANTY IN YEARS | 2 |
| | | ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not require |

0.000 h at 25°C ETIM GRUPPEN-ID EC001744 **MATERIAL COVER** Plastic matt/satinized DIMMING 0-10 V No DIMMING 1-10 V No DIMMING DALI No DIMMING DMX No DIMMING DSI No DIMMING POTENTIOMETER No (INTEGRATED) DIMMING LINESWITCH No



DIMMING MANUFACTURER'S No PROPRIETARY SYSTEM DIMMING MAINS VOLTAGE No MODULATION DIMMING PHASE CUT-OFF No DIMMING PROGRAMMABLE No **DIMMING RF** No DIMMING SINE WAVE REDUCTION No **DIMMING TOUCH AND DIM** No DIMMING ZIGBEE No **DIMMING WITH PUSH-BUTTON** No DIMMING DEPENDING ON CONTROL No GEAR NO DIM FUNCTION Yes COLOUR CONSISTENCY (MCADAM ELLIPSE) SDCM6 **DIMMING DALI-2** No DIMMING PHASE CUT-ON No DIMMING GPRS No **BEG FUNDING** Only relevant in Germany **ENERGIEEFFIZIENZKLASSE DER** G LICHTQUELLE EINER LEUCHTE **COLOUR OF LIGHT ADJUSTABLE** No