

PRODUCT NO. 600100

DOTLUX LED recessed panel SQUAREeco IP20 22W 4000K 224x224mm bundle 5 pcs.



to the product page

- Flat design with integrated power supply enables use even in difficult installation locations
- Backlight technology in robust design
- Sturdy mounting brackets ensure a secure hold
- Set of 5

SUCCESSION ARTICLE	5095-140120
PREDECESSOR ARTICLE	1963-1 1963-030120 1963-040120 1963-0FW120
WEIGHT IN KG	1.1
NET LUMINOUS FLUX IN LUMENS	1980
POWER CONSUMPTION IN WATTS	22
LUMEN PER WATT	90

Dimensions

width: 224mm
height: 28mm
length: 224mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 20.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,7
LUMEN PER WATT	90
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
SWITCH CYCLES	> 40.000
INSTALLATION OPENING WIDTH IN MM	200
INSTALLATION OPENING DIAMETER IN MM	190-200
INSTALLATION OPENING LENGHT IN MM	200
WARRANTY IN YEARS	2
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
MATERIAL COVER	Plastic matt/satinized
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No

DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
COLOUR OF LIGHT ADJUSTABLE	No