

PRODUCT NO. 5218-1

LED power supply CV 24V 12-30W <0.19A dimmable DALI IP20







to the product page

- The power supply is dimmable via DALI
- With constant voltage (CV) technology, it is suitable for constant voltage luminaires
- The connected constant voltage luminaires can be dimmed between 1%-100%.

| SUCCESSION ARTICLE | - | PROTECTION CLASS (IP) | IP20 |
|----------------------------|-------|--|--------------------------|
| | | INPUT VOLTAGE | 220 - 240 V AC |
| WEIGHT IN KG | 0.12 | SERVICE LIFE | approx. 50.000 h at 25°C |
| POWER CONSUMPTION IN WATTS | 12-30 | INRUSH CURRENT IN A | 0 |
| | | PROTECTION CLASS | 11 |
| | | SUITED FOR EMERGENCY LIGHTING | No |
| | | OUTPUT VOLTAGE | 24 |
| Dimensions | | WARRANTY IN YEARS | 3 |
| | | DIMMING WITHOUT DIMMER | No |
| length: 300mm | | ETIM GRUPPEN-ID | EC002710 |
| width: 30mm | | DIMMING 0-10 V | No |
| height: 16mm | | DIMMING 1-10 V | No |
| | | DIMMING DALI | Yes |
| | | DIMMING DMX | No |
| | | DIMMING DSI | No |
| | | DIMMING POTENTIOMETER (INTEGRATED) | No |
| | | DIMMING LINESWITCH | No |
| | | DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| | | DIMMING MAINS VOLTAGE MODULATION | No |
| | | DIMMING PHASE CUT-OFF | No |
| | | DIMMING PROGRAMMABLE | No |
| | | DIMMING RF | No |
| | | DIMMING SINE WAVE REDUCTION | No |
| | | DIMMING TOUCH AND DIM | No |



| DIMMING ZIGBEE | No | |
|-------------------------------------|--------------------------|--|
| DIMMING WITH PUSH-BUTTON | No | |
| NO DIM FUNCTION | No | |
| SUITABLE FOR EMERGENCY LIGHTING | No | |
| CONSTANT LIGHT OUTPUT (CLO) | No | |
| OPERATION BY BLUETOOTH | No | |
| COMPATIBLE WITH CASAMBI | No | |
| COMPATIBLE WITH APPLE HOMEKIT | No | |
| COMPATIBLE WITH GOOGLE ASSISTANT | No | |
| COMPATIBLE WITH AMAZON ALEXA | No | |
| IFTTT SUPPORT AVAILABLE | No | |
| SUITABLE FOR CONSTANT VOLTAGE | Yes | |
| SUITABLE FOR CONSTANT CURRENT | No | |
| DIMMING PHASE CUT-ON | No | |
| DIMMING GPRS | No | |
| PULSE DURATION IN μ S | 0 | |
| BEG FUNDING | Only relevant in Germany | |