

PRODUCT NO. 4869-050090-B-Ware

DOTLUX LED high bay spotlight LIGHTSHOWERclean 150W 5000K DALI dimmable



to the product page

- optimized light distribution due to glare-reduced lens optics and additional glare control on the housing side
- cooling finless design due to extra large die-cast aluminum housing for perfect thermal management
- suitable for use in food processing plants (HACCP)
- cover made of impact-resistant, shatterproof polycarbonate IK10
- protected against strong water jets and high pressure/steam jet cleaning (IP66/IP69)
- sustainable, repairable product design

SUCCESSION ARTICLE	in Arbeit
WEIGHT IN KG	8.9
LUMEN PER WATT	140
POWER CONSUMPTION IN WATTS	150
NET LUMINOUS FLUX IN LUMENS	21000

Dimensions

BEAM ANGLE	90°
PROTECTION CLASS (IP)	other IP66 / IP69
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	5000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,92
INRUSH CURRENT IN A	0
IK PROTECTION	IK10
LUMEN PER WATT	140
PROTECTION CLASS	I
HOUSING COLOUR	white
SWITCH CYCLES	> 100.000
FOOD-READY	Yes
OVERVOLTAGE PROTECTION	up to 6000 V
INPUT VOLTAGE SPAN	100-240 V AC
WARRANTY IN YEARS	0
INPUT VOLTAGE RANGE LUMINAIRE	100-240 V AC
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
DIMMING DALI	Yes
IMPACT STRENGTH	IK10
PULSE DURATION IN µS	0