

PRODUCT NO. 5406

DOTLUX LED rescue light EXITflat with self-test 3W 6000K incl. 4 pictograms



to the product page

- For wall mounting with LED light surface on one side
- Replaceable rechargeable battery (LiFePO4) with a lighting duration of 3 hours
- Different switching programs selectable: continuous or standby switching
- Power consumption in standby mode less than 0.5 Watt
- Automatic self-test function with integrated operating status control LED
- Including standard pictograms (left, right, up, down)
- The luminaire has integrated escape route lighting

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3649
WEIGHT IN KG	0.7
POWER CONSUMPTION IN WATTS	3
NET LUMINOUS FLUX IN LUMENS	AC 38 / Akku 29
LUMEN PER WATT	13

Dimensions

length: 325mm
width: 187mm
height: 31mm

BEAM ANGLE	180°
PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
RANGE OF SENSOR	30
COLOR TEMPERATURE IN KELVIN	6000
COLOR-RENDERING-INDEX	CRI > 70
POWER FACTOR	0,5
LUMEN PER WATT	13
PROTECTION CLASS	I
HOUSING COLOUR	multicoloured
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	3
L80/B10	50000
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC001957
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
LIFETIME L90/B50 AT 25°C	33333
BEG FUNDING	Only relevant in Germany

ENERGIEEFFIZIENZKLASSE DER
LICHTQUELLE EINER LEUCHTE

-

MATERIAL COVER

Other