

PRODUCT NO. 4873-150045

**DOTLUX LED floodlight HLFplus 1200W 5000K 1-10V dimmable 45° beam angle**



The compact high-power floodlight HLFplus is ideal for sports and soccer fields, large parking lots, construction site and crane lights, and much more.

- Extremely flexible application possibilities due to different beam angles (10°, 15°, 30°, 45°, 60°, 100°x38°)
- Excellent light distribution with minimum ULR values and low light scattering losses due to asymmetrical beam angle 100°x38°.
- Safe operation outdoors thanks to powder-coated housing with high IP protection (IP66) and real glass cover
- Very high operational safety thanks to integrated Multi Driver Technology: each spotlight has several independent power supplies with integrated overvoltage protection 10KV and 7 years DOTLUX warranty with an above average lifetime: L80>80.000h
- Adjustable brackets for hanging, standing and wall mounting included
- Dimming function available on request (FUNK/ZIGBEE/DMX/DALI)
- This luminaire is flicker-free and therefore also suitable for high-definition (HD) TV recordings
- Sustainable product design due to easily replaceable components
- Other light colors can be ordered from 1pc onwards

SUCCESSION ARTICLE	-	BEAM ANGLE	45°
PREDECESSOR ARTICLE	4873-050045	PROTECTION CLASS (IP)	IP66
		LIGHT COLOR	white
WEIGHT IN KG	27.8	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	136	SERVICE LIFE	approx. 80.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	163000	COLOR TEMPERATURE IN KELVIN	5000
POWER CONSUMPTION IN WATTS	1200	COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,97
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK08
		LUMEN PER WATT	136
Dimensions		PROTECTION CLASS	I
width: 668mm		VOLTAGE TYPE	AC/DC
height: 270mm		HOUSING COLOUR	gray
length: 731mm		SUITED FOR EMERGENCY LIGHTING	yes
		SWITCH CYCLES	> 160.000
		OVERVOLTAGE PROTECTION	up to 10000 V
		WARRANTY IN YEARS	7
		L80/B10	80000
		SUITABLE FOR SURFACE MOUNTING	No
		SUITABLE FOR MOUNTING	No
		DIMMING WITHOUT DIMMER	No
		ASSORTMENT	Proline

<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
<b>LIFETIME L80/B10 AT 25°C</b>	80000
<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	160000
<b>ETIM GRUPPEN-ID</b>	EC001744
<b>WITH ILLUMINANT</b>	Yes
<b>SUITABLE FOR WALL MOUNTING</b>	Yes
<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
<b>SUITABLE FOR CEILING MOUNTING</b>	No
<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
<b>LAMP HOLDER</b>	-
<b>MATERIAL COVER</b>	Glass transparent
<b>TYPE OF CONTROL GEAR</b>	LED operating device current- controlled
<b>WITH CONTROL GEAR</b>	Yes
<b>DIMMING 0-10 V</b>	Yes
<b>DIMMING 1-10 V</b>	Yes
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	No
<b>LIGHT DISTRIBUTOR</b>	Reflector
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>IMPACT STRENGTH</b>	IK08
<b>LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24</b>	No
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>FILAMENT TEST ACCORDING TO IEC 60695-2-11</b>	-
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	No
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	Yes
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No

COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
REFLECTOR	-
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	No
SUITABLE FOR LIGHT-TRACK MOUNTING	No
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	Yes
SUITABLE FOR TRAVERSE MOUNTING	Yes
EXCHANGEABLE CONTROL GEAR	Yes
LAMP TYPE	LED
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	160000
LIFETIME L90/B10 AT 25°C	40000
PULSE DURATION IN µs	0
LIFETIME L90/B50 AT 25°C	54000
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
ADJUSTABILITY	Rotatable
LIGHT SHARING	Symmetric
SURFACE PROTECTION	Powder coating
BEAM ANGLE	Wide beam 41-80°
CONNECTION TYPE	Free conductor end